

PC-U6A-C0424-BU-002M

Description

Osilan's Cat6A Patch Cords are part of cat6A cable solutions that are flexible and cost-effective solutions that fully comply with category 6A/ Class EA standards. Cat6A Patch cords are available in U/UTP, U/FTP and F/FTP shielded cable and with PVC or LSZH sheath, which are ideal for most of today's LAN network requirements and specifications with designs that support 500 MHz applications.

Features

- Category 6A U/UTP patch cord.
- · PVC Sheath.
- · Wired to T568B wiring schemes.
- · 4 Pairs, 24 AWG solid copper conductors.
- Supports IEEE 802.bt type 3,4 & PoE++ Standards.
- Each patch cord is 100% performance tested to component limits.

Application

- Suitable for all category 6A backbone and horizontal Cabling applications.
- 10 Base-T (Ethernet), 100 Base-T (Fast Ethernet), 1000 Base-T (Gigabit Ethernet) and 10G Base-T (10Gigabit Ethernet).
- 155Mb/s ATM, 622Mb/s ATM, 1.2Gb/s ATM, Token Ring 4/16 & ISDN.
- IEEE 802.3af, IEEE 802.3at, IEEE 802.bt type 3 and 4.


Standards

- ANSI/TIA-568-C.2 Category 6A
- EN 50173-1
- ISO 11801 2nd Edition
- EN50288-6-1

| Technical Specifications | | | | |
|--|---------------------------------------|--|--|--|
| Central Element | Cross Section - Solid Polyethylene PE | | | |
| Conductor | 24AWG Stranded Bare Copper | | | |
| Insulation | HDPE | | | |
| Pairs | 4 Twisted Pairs | | | |
| Sheath | PVC Sheath | | | |
| Outer Diameter | 5.8mm (+/- 0.2mm) | | | |
| Identification | Pair 1: White Blue / Blue | | | |
| | Pair 2: White Orange / Orange | | | |
| | Pair 3: White Green / Green | | | |
| | Pair 4: White Brown / Brown | | | |
| Connector | RJ45 8P8C including boot | | | |
| Wiring Standards | T568B wiring | | | |
| Temperature (Installation) | -30°C to +50°C | | | |
| Temperature (Operation) -20°C to +75°C | | | | |

| Mechanical and Electrical Specific | ication |
|------------------------------------|--|
| Min Bend Radius | Operation: 23.2mm (4* Outer Diameter) |
| Standard Length | 0.5m,1m,2m,3m,5m,7.5m,10m,15m,20m,30m |
| Mating Cycle | Minimum 750 |
| | |

Technical Drawings



CATEGORY 64 II/IITP PATCH CORDS 24 AWG PV

| CATEGORY CACACITY TATOR CORDS, 24 ANG, 1 TO | | | | | |
|---|--|--|--|--|--|
| Part No. | | Description | | | |
| PC-U6A-C0424-BU-002M | | Category 6A U/UTP Patch Cords, PVC Sheath, 2 m, Blue | | | |

^{*} More colours are available.

