#### **CATEGORY 6A COPPER PATCH CORDS**

the second second



## PC-U6A-H0426-WH-002M

#### Description

Osilan's Cat6A Patch Cords are part of cat6A cable solutions that are flexible and cost-effective solutions that fully comply with category 6A/ Class EA standards. Cat6A Patch cords are available in U/UTP, U/FTP and F/FTP shielded cable and with PVC or LSZH sheath, which are ideal for most of today's LAN network requirements and specifications with designs that support 500 MHz applications.

#### Features

- Category 6A U/UTP patch cord.
- LSZH Sheath.
- Wired to T568B wiring schemes.
- 4 Pairs, 26 AWG solid copper conductors.
- Supports IEEE 802.bt type 3,4 & PoE++ Standards.
- · Each patch cord is 100% performance tested to component limits.

## Application

- Suitable for all category 6A backbone and horizontal Cabling applications.
- 10 Base-T (Ethernet), 100 Base-T (Fast Ethernet), 1000 Base-T (Gigabit Ethernet) and 10G Base-T (10Gigabit Ethernet).
- 155Mb/s ATM, 622Mb/s ATM, 1.2Gb/s ATM, Token Ring 4/16 & ISDN.
- IEEE 802.3af, IEEE 802.3at, IEEE 802.bt type 3 and 4.

## Standards

- ANSI/TIA-568-C.2 Category 6A
- ISO 11801 2<sup>nd</sup> Edition
- IEC 619352

EN 50173-1EN 60332-1

• IEC 60603-7

UL444UL1581UL1666


#### Technical Specifications

| Central Element            | Cross Section - Solid Polyethylene P                  |  |  |  |
|----------------------------|---|--|--|--|
| Conductor                  | 26AWG Stranded Bare Copper<br>HDPE<br>4 Twisted Pairs |  |  |  |
| Insulation                 |   |  |  |  |
| Pairs                      |   |  |  |  |
| Sheath                     | LSZH (LSZH IEC 60332-1 Sheath)                        |  |  |  |
| Outer Diameter             | 5.2mm (+/- 0.2mm)                                     |  |  |  |
| Identification             | Pair 1: White Blue / Blue                             |  |  |  |
|                            | Pair 2: White Orange / Orange                         |  |  |  |
|                            | Pair 3: White Green / Green                           |  |  |  |
|                            | Pair 4: White Brown / Brown                           |  |  |  |
| Connector                  | RJ45 8P8C including boot                              |  |  |  |
| Wiring Standards           | T568B wiring  |  |  |  |
| Temperature (Installation) | -30°C to +50°C  |  |  |  |
| Temperature (Operation)    | -20°C to +75°C  |  |  |  |
|                            |   |  |  |  |

### Mechanical and Electrical Specification

| Min Bend Radius Operation: 23.2mm (4* Outer Diamet |                                       |
|--|---------------------------------------|
| Standard Length                                    | 0.5m,1m,2m,3m,5m,7.5m,10m,15m,20m,30m |
| Mating Cycle                                       | Minimum 750                           |

# **Technical Drawings**



| CATEGORY 6A U/UTP PATCH CORDS, 26 AWG, LSZH |  |             |  |  |  |  |
|---|--|-------------|--|--|--|--|
| Part No.                                    |  | Description |  |  |  |  |
|   |  |             |  |  |  |  |

Category 6A U/UTP Patch Cords, LSZH Sheath, 2 m, White

PC-U6A-H0426-WH-002M

\* More colours are available.