CATEGORY 6A COPPER PATCH CORDS



PC-U6AF-H0426-BU-003M

Description

Osilan's Cat6A Patch Cords are part of cat6A cable solutions that are flexible and cost-effective solutions that fully comply with category 6A/ Class EA standards. Cat6A Patch cords are available in U/UTP, U/FTP and F/FTP shielded cable and with PVC or LSZH sheath, which are ideal for most of today's LAN network requirements and specifications with designs that support 500 MHz applications.

Features

- Category 6A U/FTP patch cord.
- LSZH Sheath.
- Wired to T568B wiring schemes.
- 4 Pairs, 26 AWG solid copper conductors.
- Supports IEEE 802.bt type 3,4 & PoE++ Standards.
- · Each patch cord is 100% performance tested to component limits.

Application

- Suitable for all category 6A backbone and horizontal Cabling applications.
- 10 Base-T (Ethernet), 100 Base-T (Fast Ethernet), 1000 Base-T (Gigabit Ethernet) and 10G Base-T (10Gigabit Ethernet).
- 155Mb/s ATM, 622Mb/s ATM, 1.2Gb/s ATM, Token Ring 4/16 & ISDN.
- IEEE 802.3af, IEEE 802.3at, IEEE 802.bt type 3 and 4.

Standards

- ANSI/TIA-568-C.2 Category 6A
- ISO 11801 2nd Edition
- IEC 619352

• EN 50173-1 • EN 60332-1

• IEC 60603-7


• UL444 • UL1581 • UL1666

| Technical Specifications | | | |
|----------------------------|---------------------------------------|--|--|
| Central Element | Cross Section - Solid Polyethylene PE | | |
| Conductor | 26AWG Stranded Bare Copper | | |
| Insulation | HDPE | | |
| Pairs | 4 Twisted Pairs | | |
| Sheath | LSZH (LSZH IEC 60332-1 Sheath) | | |
| Outer Diameter | 5.8mm (+/- 0.3mm) | | |
| Identification | Pair 1: White Blue / Blue | | |
| | Pair 2: White Orange / Orange | | |
| | Pair 3: White Green / Green | | |
| | Pair 4: White Brown / Brown | | |
| Connector | RJ45 8P8C including boot | | |
| Wiring Standards | T568B wiring | | |
| Temperature (Installation) | -30°C to +50°C | | |
| Temperature (Operation) | -20°C to +75° | | |
| | | | |

Mechanical and Electrical Specification

| Min Bend Radius | Operation: 23.2mm (4* Outer Diameter) |
|-----------------|--|
| Standard Length | 0.5m,1m,2m,3m,5m,7.5m,10m,15m,20m,30m |
| Mating Cycle | Minimum 750 |
| | |

Technical Drawings



| CATEGORY 6A U/FTP PATCH CORDS, 26 AWG, LSZH | | | | |
|---|--|--|--|--|
| Part No. | | Description | | |
| PC-U6AF-H0426-BU-003M | | Category 6A U/FTP Patch Cord, LSZH Sheath, 3 m, Blue | | |

* More colours are available.

