

PC-U6AF-H0426-IG-003M

Description

Osilan's Cat6A Patch Cords are part of cat6A cable solutions that are flexible and cost-effective solutions that fully comply with category 6A/ Class EA standards. Cat6A Patch cords are available in U/UTP, U/FTP and F/FTP shielded cable and with PVC or LSZH sheath, which are ideal for most of today's LAN network requirements and specifications with designs that support 500 MHz applications.

Features

- Category 6A U/FTP patch cord.
- · LSZH Sheath.
- · Wired to T568B wiring schemes.
- · 4 Pairs, 26 AWG solid copper conductors.
- Supports IEEE 802.bt type 3,4 & PoE++ Standards.
- Each patch cord is 100% performance tested to component limits.

Application

- Suitable for all category 6A backbone and horizontal Cabling applications.
- 10 Base-T (Ethernet), 100 Base-T (Fast Ethernet), 1000 Base-T (Gigabit Ethernet) and 10G Base-T (10Gigabit Ethernet).
- 155Mb/s ATM, 622Mb/s ATM, 1.2Gb/s ATM, Token Ring 4/16 & ISDN.
- IEEE 802.3af, IEEE 802.3at, IEEE 802.bt type 3 and 4.


Standards

ANSI/TIA-568-C.2 Category 6A	• IEC 60603-7	• UL444
• ISO 11801 2 nd Edition	• EN 50173-1	• UL1581
• IFC 619352	• EN 60332-1	• UI 1666

echnical Specifications		
Central Element	Cross Section - Solid Polyethylene PE	
Conductor	26AWG Stranded Bare Copper	
Insulation	HDPE	
Pairs	4 Twisted Pairs	
Sheath	LSZH (LSZH IEC 60332-1 Sheath)	
Outer Diameter	5.8mm (+/- 0.3mm)	
Identification	Pair 1: White Blue / Blue	
	Pair 2: White Orange / Orange	
	Pair 3: White Green / Green	
	Pair 4: White Brown / Brown	
Connector	RJ45 8P8C including boot	
Wiring Standards T568B wiring		
Temperature (Installation)	mperature (Installation) -30°C to +50°C	
Temperature (Operation) -20°C to +75°		

Mechanical and Electrical Specification		
Min Bend Radius	Operation: 23.2mm (4* Outer Diameter)	
Standard Length	0.5m,1m,2m,3m,5m,7.5m,10m,15m,20m,30m	
Mating Cycle	Minimum 750	

Technical Drawings



CATEGORY 6A U/FTP PATCH CORDS, 26 AWG, LSZH					
Part No.	Description				
PC-U6AF-H0426-IG-003M	Category 6A U/FTP Patch Cord, LSZH Sheath, 3 m, International Grey				

^{*} More colours are available.