# COPPER JACK MODULES CATEGORY 6A

# JMU6A180S-BW

#### Description

OSILAN

OSILAN Cat6A snap-in jack modules complete Category 6A/Class EA components and performance. The RJ-45 jack modules are suitable for mounting in a range of housings from patch panels, faceplates, floor boxes, and work area distribution enclosures

#### Features

- RJ-45 jack Modules are available with multiple colours
- Contacts plated with 50 micro inches of gold.
- Wiring Code: T568A and T568B wiring schemes.
- Terminates full range of 23 26 AWG conductors
- High-impact, fire-retardant plastic connector body
- Spring shuttered jack module to prevent dust
- Termination style can be done without tools (Tool-less type).

## Application

- Suitable for all category 6A backbone and horizontal Cabling applications.
- 10 Base-T (Ethernet), 100 Base-T (Fast Ethernet), 1000 Base-T (Gigabit Ethernet) and 10G Base-T (10Gigabit Ethernet).

• EN 50173-1

- 155Mb/s ATM, 622Mb/s ATM, 1.2Gb/s ATM, Token Ring 4/16 & ISDN.
- IEEE 802.3af, IEEE 802.3at, IEEE 802.bt type 3 and 4.


### Standards

- ANSI/TIA-568-C.2 Category 6A
- ISO 11801 2<sup>nd</sup> Edition

#### Technical Specifications

RJ 45 Jack Housing	Polycarbonate (PC) + Acrylonitrile-Butadiene-Styrene (ABS)
RJ45 Jack Contact	Phosphor bronze, Nickel Plated. Gold Plated on Plug area
IDC Housing	Polycarbonate (PC)
IDC Terminal	Phosphor Bronze, Tin Plated
IDC Cap	Polycarbonate (PC)
PCB: FR4, Thickness	1.6 mm
Wiring Code	T568A & T568B
Termination Style	IDC compatible without tools
Operating Temperature	-10°C to 60°C
Storage Temperature	-40°C to 70°C

# **Technical Drawings**



#### Mechanical and Electrical Specification Life time Minimum 750 Insertion Cycle Number of IDC Termination Minimum 200 reterminations Insertion Force Maximum 20N Retention Strength 7.7 Kg between Jack and Plug Insulation Resistance Minimum 1000 MΩ 750Vac/RMS/60Hz for 1min Dielectric withstand voltage Contact Resistance $\text{Maximum 100} \text{ m}\Omega$ Current Rating 1.5 Amp @ 20° C

# COVER



CATEGORY 6A UTP KEYSTONE JACK WITH SHUTTER			
Part No.		Description	
JMU6A180S-BW		Category 6A Unscreened Keystone Jack with Shutter - Black & White	

\* More colours are available.



