

COPPER JACK MODULES CATEGORY 6A

JMU6A180S-WH

Description

OSILAN Cat6A snap-in jack modules complete Category 6A/Class EA components and performance. The RJ-45 jack modules are suitable for mounting in a range of housings from patch panels, faceplates, floor boxes, and work area distribution enclosures





Features

- RJ-45 jack Modules are available with multiple colours
- · Contacts plated with 50 micro inches of gold.
- Wiring Code: T568A and T568B wiring schemes.
- Terminates full range of 23 26 AWG conductors
- · High-impact, fire-retardant plastic connector body · Spring shuttered jack module to prevent dust
- Termination style can be done without tools (Tool-less type).

Application

- Suitable for all category 6A backbone and horizontal Cabling applications.
- 10 Base-T (Ethernet), 100 Base-T (Fast Ethernet), 1000 Base-T (Gigabit Ethernet) and 10G Base-T (10Gigabit Ethernet).
- 155Mb/s ATM, 622Mb/s ATM, 1.2Gb/s ATM, Token Ring 4/16 & ISDN.
- IEEE 802.3af, IEEE 802.3at, IEEE 802.bt type 3 and 4.

Standards


- · ANSI/TIA-568-C.2 Category 6A
- EN 50173-1
- ISO 11801 2nd Edition

Technical Specifications	
RJ 45 Jack Housing	Polycarbonate (PC) + Acrylonitrile-Butadiene-Styrene (ABS)
RJ45 Jack Contact	Phosphor bronze, Nickel Plated. Gold Plated on Plug area
IDC Housing	Polycarbonate (PC)
IDC Terminal	Phosphor Bronze, Tin Plated
IDC Cap	Polycarbonate (PC)
PCB: FR4, Thickness	1.6 mm
Wiring Code	T568A & T568B
Termination Style	IDC compatible without tools
Operating Temperature	-10°C to 60°C
Storage Temperature	-40°C to 70°C

Mechanical and Electrical Specification	
Minimum 750 Insertion Cycle	
Minimum 200 reterminations	
Maximum 20N	
7.7 Kg between Jack and Plug	
Minimum 1000 MΩ	
750Vac/RMS/60Hz for 1min	
Maximum 100 mΩ	
1.5 Amp @ 20° C	

Technical Drawings







COVER











CATEGORY 6A UTP KEYSTONE JACK WITH SHUTTER

Part No. Description JMU6A180S-WH Category 6A Unscreened Keystone Jack with Shutter - White



^{*} More colours are available.