

## JMU61802-WH

### Description

OSILAN Cat6 snap-in jack modules complete Category 6/Class E components and performance. The RJ-45 jack modules are suitable for mounting in a range of housings from patch panels, faceplates, floor boxes, and work area distribution enclosures.

### Features

- RJ-45 jack Modules are available with multiple colours
- Contacts plated with 50 micro inches of gold.
- Wiring Code: T568A and T568B wiring schemes.
- Terminates full range of 22 – 26 AWG conductors
- High-impact, fire-retardant plastic connector body
- Spring shuttered jack module to prevent dust or debris from accumulating on contacts.
- Termination style can be done without tools (Tool-less type) or with 110 Compatible tools.

### Application

- Suitable for all category 6 backbone and horizontal Cabling applications.
- 10 Base-T (Ethernet), 100 Base-T (Fast Ethernet), 1000 Base-T (Gigabit Ethernet).
- 155Mb/s ATM, 622Mb/s ATM, 1.2Gb/s ATM, Token Ring 4/16 & ISDN

### Standards

- ANSI/TIA-568.2-D Category 6
- ANSI/TIA-568-C.2 Category 6
- ISO 11801 2<sup>nd</sup> Edition
- EN 50173-1

#### Technical Specifications

Resistance	30 mOhm
Mating Cycles	2000 cycle
Mating Force	20 N
Contact material	Phosphor Bronze
Flammability Rating	UL 94V-0

#### CATEGORY 6 UTP KEYSTONE JACK, TOOL-LESS VERSION

Part No.	Description
JMU61802-WH	Category 6 Unscreened Tool-less Keystone Jack - White

\* More colours are available.

