

**FPC-OM2STSTD005M**

## Description

Osilan's fibre optic patch cords are the optimal choice for Enterprise inter-connect, data centre and cross-connect applications. Patch cords complete connectivity from active equipment to passive optical equipment in main or distribution rack rooms. Fibre optic patch cords are available in OM2, OM3, OM4 or OS2 fibre types terminated with ultra-physical contact (UPC) zirconia ferrule connectors to meet the demands of all Ethernet applications.



## Features

- Duplex jacketed zip cord tight buffered.
- Standard low-insertion loss connectors.
- Halogen-free, flame-retardant LSZH jacket.
- Ferrules of Zirconia ceramic with high performance.
- Both Connectors A and B are ultra-physical contacts (UPC).

## Standards

ISO 11801 2nd Edition	EN 60332-1	ANSI/ICEA S-83-596
TIA 568 C.3	IEC 61034-2	CSA FT4
EN 50173	IEC 60794-2	CSA FT6
EN 50575: Euroclass Eca		

Mechanical and Environmental Characteristics	
Cable outside diameter	3mm Simplex 1.8mm Duplex
Cable retention	50N
Endurance	500 mating cycles
Minimum Bend radius	30mm Simplex 18mm Duplex
Temperature range	-20°C to +60°C
Operating Temperature	-40°C to +70°C
Storage Temperature	-40°C to +70°C

Cable & Connector Parameters	
Items	Specifications
<b>Connector</b>	
LC Connector	Blue
Boot	white
SC Connector	Blue
Boot	Blue
FC Connector	metal
Boot	Black
ST Connector	metal
Boot	Red / Black
<b>Cable</b>	
Simplex	1 fiber core
Duplex	2 fiber cores
water-blocking system	
Material	Aramid Yarn
Outer Jacket	
Material	LSZH
Colour	OS2: Yellow OM2: Orange OM3: Aqua OM4: Violet

Fibre Parameters	
Items	Specifications
Cladding Diameter	124.8±0.7 µm
Cladding Non-Circularity	≤0.7%
Core-Cladding Concentricity Error	≤0.5 µm
Coating Diameter	245±5 µm
Coating Non-Circularity	≤6.0%
Cladding-Coating Concentricity Error	≤12.0 µm
ITU-T Standards	G.652.D or G.657.A1 for SM G.651.1 for MM
Attenuation	1310nm ≤0.36 dB/km
	1550nm ≤0.25 dB/km
	850 nm ≤3 dB/km 1300nm ≤1 dB/km
connector insertion loss	< 0.5 dB (Standard Multimode) < 0.3 dB (Standard Singlemode)
connector return loss	> 40 dB (Standard Multimode) > 50 dB (Standard Singlemode)

## ORDERING INFORMATION

Part No.	Description
FPC-OM2STSTD005M	ST/UPC to ST/UPC, Duplex fibre optic patch cords, OM2, 1.8mm jacket, Orange, low smoke zero halogens (LSZH), 5 meter